


PROPRIETARY NOTICE

This document discloses confidential subject matter in which MilesTek Corporation and its subsidiaries have proprietary rights. Neither receipt nor possession thereof confers or transfers any right to reproduce or disclose the document, any part thereof, any information contained therein, or any physical article or device, or to practice any method or process, except by written permission from, or written agreement with MilesTek Corporation and its subsidiaries.



NOTES:


1. MATERIAL:  
EXTERNAL PARTS: ALUMINUM/BLACK ANODIZE  
ADAPTER HOUSING: THERMOPLASTIC  
MISC. HARDWARE: STAINLESS STEEL  
SEALS: SILICONE / NITRILE  
LANYARD: STAINLESS STEEL (NYLON COAT)
2. RATING: IP-68 WHEN MATED OR CAPPED PROPERLY
3. APPLICATION: SINGLE MODE, APC POLISH
4. ALL DIMENSIONS ARE FOR REFERENCE ONLY.
5. COMPONENT SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH MILESTEK SPECIFICATION PS-0054

**REGULATORY COMPLIANCE:**  
CE2011/65/EU(RoHS DIRECTIVE)

REV	REVISIONS		DATE	APPROVED
	DESCRIPTION			
A	REV A DRAWING RELEASED		06/11/18	B.PUCHASKI

Parameter	Specification	Performance
Insertion Loss (IL) (UPC)	EIA/TIA-455-171	0.25dB - Typical; 0.50dB - Maximum
Return Loss (RL) (UPC)	EIA/TIA-455-107A	Minimum 0.50dB
Operational Temperature	EIA/TIA-455-5C	-40°C to +85°C
Storage Temperature	EIA/TIA-455-5C	-40°C to +85°C
Temperature Humidity Cycling	EIA/TIA-455-5C	-40°C to +71°C at 95% RH, 240 hrs.
Dust Test	IEC 60529 IP68	8 hrs dust exposure with 20 mbar
Water Submersion	IEC 60529 IP68	48 hrs. immersion/1 meter water
Cable Retention <sup>1</sup>	EIA/TIA-455-6	400 lbs. for 10 minutes
Mating Durability	EIA/TIA-455-21	500 cycles
Impact	EIA/TIA-455-2C	8 drops, 2.4 meters
Vibration	EIA/TIA-455-11	10-55Hz, 2 hr/axis, 3 axis
Mechanical Shock	EIA/TIA-455-14A	Condition C, 5 shocks/axis
Crush	EIA/TIA-455-26A	450 lbs.

NON CONTROLLED DRAWING IF PRINTED

			CAD SYSTEM DRAWING - DO NOT REVISE MANUALLY			
			UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES	SIGNATURE	DATE	 <div>MILESTEK CORPORATION 301 LEORA LANE, SUITE 100 LEWISVILLE, TX 75056 PHONE: (940) 484-9400 FAX: (940) 566-1047</div>
			OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 ≤12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0%	DRAWN BY: B.PUCHASKI	06/07/18	
			ALL OTHER DIMENSIONAL TOLERANCES: X = ±.2 [5.08] XX = ±.02 [5.1] XXX = ±.005 [13]	CHECKED BY: J.LABOY	06/07/18	TITLE
			CUSTOMER REFERENCE DOCUMENT:	APPROVED ENGINEERING: D.GUITADAURO	06/07/18	LC IP68 RCPT D38999 SM APC DCAP
				APPROVED MANUFACTURING:		
				CUSTOMER APPROVAL		
DASH	NEXT ASSY	USED ON				SIZE A
APPLICATION				CAGE CODE: 42977		DRAWING NUMBER: FYC00017
					SCALE: NTS	SHEET 1 OF 1