

Bulk Cable Specification

FINISHED GOOD PART NUMBER
 CSLSZH09-100 100 FOOT COIL
 CSLSZH09-500 500 FOOT SPOOL
 CSLSZH09-1000 1000 FOOT SPOOL

PRODUCTION PART NUMBER
 1AL08-033

<p>Cross-Sectional View</p> <p>DRAIN</p> <p>JACKET</p> <p>CONDUCTOR</p> <p>SHIELD</p> <p>BRAID SHIELD</p>	<p>Color Code</p> <ol style="list-style-type: none"> 1. BLACK 2. RED 3. WHITE 4. GREEN 5. ORANGE 6. BLUE 7. WHITE / BLACK 8. RED / BLACK 9. GREEN / BLACK
--	--

No of Conductors		9
Conductor	Material	Stranded Tinned Copper
	Construction	24 AWG (7/32)
Insulation	Material	High Density Polyethylene
	Nominal Thickness	.012"
Shielding	Coverage	100% Coverage
	Material	Aluminum Polyester (foil facing out)
Drain Wire	Construction	24 AWG (7/32)
	Material	Stranded Tinned Copper
Braiding	Coverage	65% coverage (minimum)
	Material	36 AWG Tinned Copper Wire
Jacket	Nominal Thickness	.025"
	Nominal Diameter	.251"
	Material	Low Smoke Zero Halogen
	Color	Black

Minimum Marking: L-COM LOW SMOKE ZERO HALOGEN - 9/C 24 AWG IEC 332 PART 1 IEC 754 IEC 1034
 – (lot designator)

ELECTRICAL PROPERTIES

DC Resistance	26.2 Ω/M'
DC Rating	30V (Min)
Capacitance	18.5pF / ft (mutual)
Dielectric Withstanding Voltage	1500 V rms
Temperature Rating (max)	60°C

Regulatory Compliance: CE2011/65/EU (RoHS DIRECTIVE) △E