

**Bulk Cable Specification**

Cross-Sectional View		Color Code
		<ol style="list-style-type: none"> <li>1. BLACK</li> <li>2. RED</li> <li>3. WHITE</li> <li>4. GREEN</li> <li>5. ORANGE</li> <li>6. BLUE</li> <li>7. WHITE / BLACK</li> <li>8. RED / BLACK</li> <li>9. GREEN / BLACK</li> <li>10. ORANGE / BLACK</li> <li>11. BLUE / BLACK</li> <li>12. BLACK / WHITE</li> <li>13. RED / WHITE</li> <li>14. GREEN / WHITE</li> <li>15. BLUE / WHITE</li> </ol>
No. of Conductors		15
Conductor	Material	Stranded Tinned Copper
	Construction	24 AWG (7/32)
Insulation	Material	High Density Polyethylene
	Nominal Thickness	.012"
Shield	Coverage	100% Coverage
	Material	Aluminum Polyester (foil facing out)
Drain Wire	Construction	24 AWG (7/32)
	Material	Stranded Tinned Copper
Braiding	Coverage	65% coverage (minimum)
	Material	36 AWG Tinned Copper Wire
Jacket	Nominal Thickness	.032"
	Nominal Diameter	.315"
	Material	Low Smoke Zero Halogen
	Color	Black
Minimum Marking: L-COM LOW SMOKE ZERO HALOGEN - 15/C 24 AWG IEC 332 PART 1 IEC 754 IEC 1034 – (lot designator)		
<b>ELECTRICAL PROPERTIES</b>		
DC Resistance	26.2 $\Omega$ /1000'	
Voltage Rating	300V (Max.)	
Capacitance	18.5pF / ft (mutual)	
Dielectric Withstanding Voltage	1500 V rms	
Temperature Rating (max)	60°C	
<b>PACKAGING</b>		
CSLSZH15-100:	100 ft coil in accordance with L-com specification PS-0031	
CSLSZH15-500:	500 ft spool	
CSLSZH15-1000:	1000 ft spool	