

REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	06/28/2018	DFRIBIELLO



UL STYLE 21511, 2X, TWISTED PAIR, 30AWG WITH ALUM/POLY FOIL SHIELD AND DRAIN WIRE. ONE UNSHIELDED TWISTED PAIR, 30AWG. 2 COND., 24AWG. OVERALL BRAID SHIELD, 65% JACKET: LSZH, BLACK



SERIES "A" USB 3.0 PLUG CONTACTS: 30µINCHES GOLD PLATING



MICRO-B USB 3.0 PLUG CONTACTS: 30µINCHES GOLD PLATING

MODEL NUMBER	LENGTH METERS [FEET]
MUS3A00046-03M	0.3 [.98]
MUS3A00046-05M	0.5 [1.64]
MUS3A00046-1M	1.0 [3.28]
MUS3A00046-2M	2.0 [6.56]
MUS3A00046-3M	3.0 [9.84]



SIGNATURE	DATE
DFRIBIELLO	06/28/2018
BGATES	06/28/2018

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES
OVERALL CABLE LENGTH TOLERANCE: >12 (305) 560 (1424) = +.125 / -0 >12 (305) 560 (1424) = +.151 / -0 >120 (3048) 5320 (13620) = +.152 / -0 >300 (7620) = +.3% / -0%
ALL OTHER DIMENSIONAL TOLERANCES: X = ± .010 (0.254) Y = ± .005 (0.127) XXX = ± .003 (0.076)

CUSTOMER REFERENCE DOCUMENT:
XXXXXX

APPLICATION
XXXXXX

DATE	TITLE
06/28/2018	CBL USB 3.0 A/MIC B LSZH


CAGE CODE: 42977	DRAWING NUMBER:
XXXXXX	MUS3A00046

SCALE: NTS	SHEET 1 OF 1
XXXXXX	1

PROPRIETARY NOTICE
This document discloses confidential subject matter in which Milestek Corporation and its subsidiaries have proprietary rights. Neither receipt nor possession thereof confers or warrants that any information contained therein, or any physical article or device, or to practice any method or process, except by written permission from, or written agreement with Milestek Corporation and its subsidiaries.



UL STYLE 21511, 2X, TWISTED PAIR, 30AWG WITH ALUM/POLY FOIL SHIELD AND DRAIN WIRE. ONE UNSHIELDED TWISTED PAIR, 30AWG. 2 COND., 24AWG. OVERALL BRAID SHIELD, 65% JACKET: LSZH, BLACK



SERIES "A" USB 3.0 PLUG CONTACTS: 30µINCHES GOLD PLATING



MODEL NUMBER	LENGTH METERS [FEET]
MUS3A00046-03M	0.3 [.98]
MUS3A00046-05M	0.5 [1.64]
MUS3A00046-1M	1.0 [3.28]
MUS3A00046-2M	2.0 [6.56]
MUS3A00046-3M	3.0 [9.84]



NOTES:
1. CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
2. CABLE ASSEMBLY SHALL HAVE 360° SHIELD TERMINATION.
3. CABLE ASSEMBLY MUST MEET USB 3.0 REQUIREMENTS.
4. CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH MILESTEK SPECIFICATION PS-0054.

REGULATORY COMPLIANCE:
CE2011/65/EU (ROHS DIRECTIVE)

NON CONTROLLED DRAWING IF PRINTED

CAD SYSTEM DRAWING - DO NOT REVISE MANUALLY



MILESTEK CORPORATION
3010 KENYON AVE., SUITE 100
MILFORD, MA 01860
PHONE: (949) 484-4400
FAX: (949) 564-1047