



TRB FULL CRIMP MALE PLUG

KEY	PART NUMBER	MATING INTERFACE	CABLE TYPE
A	10-06031-206	3-slot plug TRB full crimp	M17/176-00002
A	10-06031-210	3-slot plug TRB full crimp	30-02001, TWC-78-2
A	10-06031-231	3-slot plug TRB full crimp	30-02003, TWC-78-1
A	10-06031-242	3-slot plug TRB full crimp	30-02002, TWAC-78-1F2

TRB FULL CRIMP RIGHT ANGLE MALE PLUG

KEY	PART NUMBER	MATING INTERFACE	CABLE TYPE
B	10-06032-206	3-slot plug right angle full crimp	M17/176-00002
B	10-06032-210	3-slot plug right angle full crimp	30-02001, TWC-78-2
B	10-06032-231	3-slot plug right angle full crimp	30-02003, TWC-78-1
B	10-06032-242	3-slot plug right angle full crimp	30-02002, TWAC-78-1F2

TRB FULL CRIMP FEMALE JACK

KEY	PART NUMBER	MATING INTERFACE	CABLE TYPE
C	10-06576-206	3-lug jack TRB full crimp	M17/176-00002
C	10-06576-210	3-lug jack TRB full crimp	30-02001, TWC-78-2
C	10-06576-231	3-lug jack TRB full crimp	30-02003, TWC-78-1
C	10-06576-242	3-lug jack TRB full crimp	30-02002, TWAC-78-1F2

BULKHEAD FEEDTHRU JACKS

KEY	PART NUMBER	GROUNDING	MATING INTERFACE	MOUNTING HOLE DIMENSION
D	10-06567	Non-isolated	3-lug female to 3-lug female	D3.187
D	10-08567	Non-isolated	2-lug female to 2-lug female	D3.187
D	10-07567	Non-isolated	4-lug female to 4-lug female	D3.187
D	10-09567	Non-isolated	threaded female to threaded female	D3.187
E	10-06568	Isolated	3-lug female to 3-lug female	D2.140
E	10-08568	Isolated	2-lug female to 2-lug female	D2.140
E	10-07568	Isolated	4-lug female to 4-lug female	D2.140
E	10-09568	Isolated	threaded female to threaded female	D2.140

### MOUNTING HOLE SPECIFICATIONS

D	A	B
1	.755" - .760"	.343" - .346"
2	.630" - .635"	.281" - .284"
3	.505" - .510"	.218" - .221"
4	.439" - .443"	.187" - .190"

**EXAMPLE: D4.125**

Maximum panel thickness in inches Mounting hole dimensions

ISOLATED BULKHEAD JACK TO SOLDER POT

KEY	PART NUMBER	CHARACTERISTICS	MATING INTERFACE	MOUNTING HOLE DIMENSION
I	10-06571	Front Mount	3-lug female	D2.140
I	10-08571	Front Mount	2-lug female	D2.140
I	10-07571	Front Mount	4-lug female	D2.140
I	10-09571	Front Mount	threaded female	D2.140
J	10-06572	Rear Mount	3-lug female	D2.140
J	10-08572	Rear Mount	2-lug female	D2.140
J	10-07572	Rear Mount	4-lug female	D2.140
J	10-09572	Rear Mount	threaded female	D2.140

NON-ISOLATED BULKHEAD JACK TO SOLDER POT

KEY	PART NUMBER	CHARACTERISTICS	MATING INTERFACE	MOUNTING HOLE DIMENSION
F	10-06569	Front Mount	3-lug female	D4.125
F	10-08569	Front Mount	2-lug female	D4.125
F	10-07569	Front Mount	4-lug female	D4.125
F	10-09569	Front Mount	threaded female	D4.125
G	10-06592	Front Mount, no ground tab	3-lug female	D4.125
G	10-08592	Front Mount, no ground tab	2-lug female	D4.125
G	10-07592	Front Mount, no ground tab	4-lug female	D4.125
G	10-09592	Front Mount, no ground tab	threaded female	D4.125
H	10-06570	Rear Mount	3-lug female	D3.218
H	10-08570	Rear Mount	2-lug female	D3.218
H	10-07570	Rear Mount	4-lug female	D3.218
H	10-09590	Rear Mount	threaded female	D3.218

**FOR BULK CABLE OPTIONS - SEE PAGE 72**

Please contact us with any connector requirements that you may have.