



Electrical Specifications:

Impedance: 75 ohms
 Frequency Range: 0-1 GHz
 Working Voltage: 500 VRMS
 Dielectric Withstanding Voltage: 1500 VRMS
 VSWR: 1.05 + 0.1f (GHz) DC to 1 GHz
 Contact Resistance: Center Contact 1.3 milliohms,
 Outer Contact 1.0 milliohms
 Insulation Resistance: 5000 megohms (min.)

Materials:

Contact Pin, Sleeve, Body: Brass Per QQ-B-626, Alloy 360, 1/2H
 Spring: Beryllium Copper
 Insulator: Teflon MIL-P-19468

Finishes:

Contact Pin: Gold 30u" over Nickel 50u" over Copper 50u"
 Body, Sleeve & Other Brass Parts: Nickel 100u" over Copper 50u"

Milestek[®] MilesTek Corporation
 1506 Interstate 35 West
 Denton, Tx 76207

Telephone: 940.484.9400 • Toll Free: 866.524.1553
 Fax: 940.591.7086 • Web: www.milestek.com

PART NUMBER: 10-03908	CAGE CODE: 4Z977	APPROVED	MARK HEARN
TITLE: 75Ω BNC R/A ADAPTER		CHECKED	ROBERT PEREZ
UNIT: mm	DATE: 03/28/1997	SHEET: 1/1	ISO 9001: 2000 CERTIFIED