



RECOMMENDED  
MOUNTING HOLE DIMENSIONS  
(inches)

1. MAX. PANEL THICKNESS=0.122"



**Milestek**<sup>®</sup> MilesTek Corporation  
1506 Interstate 35 West  
Denton, Tx 76207

Telephone: 940.484.9400 • Toll Free: 866.524.1553  
Fax: 940.591.7086 • Web: www.milestek1553.com

<b>PART NUMBER:</b> 10-06569	<b>CAGE CODE:</b> 4Z977
<b>TITLE:</b> TRB FRONT MOUNT NON-ISOLATED BULKHEAD RECEPT JACK	
<b>UNIT:</b> mm	<b>DATE:</b> 08/2/2005
<b>REV:</b>	<b>SHEET:</b> 1/1

<b>APPROVED</b>	MARK HEARN
<b>CHECKED</b>	ROBERT PEREZ
<b>ISO 9001: 2000 CERTIFIED</b>	

UNLESS OTHERWISE  
SPECIFIED TOLERANCES:  
0.5-5 = ±0.2  
5-30 = ±0.4  
30-120 = ±0.6  
120-315 = ±1

NO	DESCRIPTION	MATERIAL
1	CONTACT BODY	BRASS/GOLD PLATE
2	INSULATOR	TEFLON
3	CONTACT PIN	BERYLLIUM COPPER GOLD PLATE 30 μ"
4	INSULATOR	TEFLON
5	INSULATOR	TEFLON
6	BODY	BRASS/NICKLE PLATE
7	LOCK RING	BRASS/NICKLE PLATE
8	TAG	BRASS/SILVER PLATE
9	WASHER	SS41/NICKEL PLATE
10	NUT	BRASS/NICKEL PLATE