



NOTE:

1. CRIMPED FERRULE HEX CRIMP SIZE .255" [6.48]
2. CRIMPED CONTACT PIN HEX CRIMP SIZE .100" [2.54] OR SOLDER.

8				UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 - 8mm ± 0.20mm 8 - 30mm ± 0.40mm 30 - 120mm ± 0.50mm  UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 - .315 = ± 0.007" .315 - 1.180 = ± 0.015" 1.180 - 4.724 = ± 0.020"	SIGNATURE	DATE	<b>MilesTek</b> MILESTEK CORPORATION 1506 INTERSTATE 35 WEST DENTON, TX 76207 PHONE: 866.524.1553 FAX: 940.591.7086
7			DRAWN BY: M. GREENHILL		10/01/2010	PART DISCRIPTION: <b>N M CRIMP RG59 &amp; RG62</b>	
6			CHECKED BY:				SIZE <b>D</b>
5			APPROVED ENGINEERING:			PART NUMBER: <b>11-N004</b>	
4			APPROVED MANUFACTURING:		REV.-A		
3	INSULATOR	PTFE	NATURAL	DRAWING NUMBER: 11-N004.PDF	CAGE CODE: 4Z977	DO NOT SCALE DRAWING	SHEET 1 OF 1
2	CONTACT PIN	BRASS	GOLD				
1	BODY	BRASS	NEXTOTE				
	DESCRIPTION	MATERIAL	FINISH				