



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

- 1. BRASS
- 2. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 50 MIN. THICK OVER COPPER PL. 50 MIN. THICK
- 3. TEFLON

1. CRIMPED FERRULE  
HEX CRIMP SIZE .128"

8				DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4	SIGNATURE	DATE	<b>MilesTek</b> MILESTEK CORPORATION 1506 INTERSTATE 35 WEST DENTON, TX 76207 PHONE: 866.524.1553 FAX: 940.591.7086	
7					DRAWN BY: M. GREENHILL	10/01/2010		PART DISCIPTION: <b>SMA MALE, CRIMP ATTACHMENT FOR          RG174, RG188 &amp; RG316</b>
6					CHECKED BY:		SIZE <b>D</b>	
5					APPROVED ENGINEERING:			PART NUMBER: <b>11-SMA006</b>
4					APPROVED MANUFACTURING:			
3	INSULATOR	TEFLON	NATURAL					
2	CONTACT PIN	BRASS	GOLD					
1	BODY	BRASS	GOLD					
	DESCRIPTION	MATERIAL	FINISH	DRAWING NUMBER: 11-SMA006.PDF	CAGE CODE: 4Z977	REV.-A	DO NOT SCALE DRAWING	SHEET 1 OF 1