



1. CRIMPED FERRULE
HEX. CRIMP SIZE .213"
2. CONTACT PIN TO SOLDER

8				DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5–6 = ±0.2 6–30 = ±0.4 30–120 = ±0.6 120–315 = ±1 315–1000 = ±1.6 1000–2000 = ±2.4	SIGNATURE	DATE	MilesTek MILESTEK CORPORATION 1506 INTERSTATE 35 WEST DENTON, TX 76207 PHONE: 866.524.1553 FAX: 940.591.7086				
7											
6							DRAWN BY: M. GREENHILL	10/01/2010	PART DISCRIPTION: SMA MALE, CRIMP ATTACHMENT FOR RG55, RG142, RG223 & RG400		
5											
4					CHECKED BY:		SIZE D PART NUMBER: 11-SMA008				
3	INSULATOR	TEFLON	NATURAL		APPROVED ENGINEERING:						
2	CONTACT PIN	BRASS	GOLD		APPROVED MANUFACTURING:						
1	BODY	BRASS	NICKEL		DRAWING NUMBER:	CAGE CODE: 4Z977		REV.-A DO NOT SCALE DRAWING SHEET 1 OF 1			
	DESCRIPTION	MATERIAL	FINISH	11-SMA008.PDF							