

**Bulk Cable Specification**

---

**RG6/U Coaxial Cable**

<b>MODEL</b>	<b>PRIMARY PACKAGING</b>	<b>SECONDARY PACKAGING</b>	<b>LENGTH</b>
RG6-100	COIL	LOGO BAG	100 FT.
RG6-500	SPOOL	STRETCH WRAP	500 FT.
RG6-1K	SPOOL	STRETCH WRAP	1000 FT.



**NOMINAL IMPEDANCE:**

75 OHMS

**CONDUCTOR MATERIAL AND DIAMETER**

18 AWG. SOLID BARE Ø.040" NOMINAL

**SHIELDING TYPE AND COVERAGE**



1<sup>ST</sup> LAYER; DUOFOIL 100% COVERAGE  
2<sup>ND</sup> LAYER; TINNED COPPER BRAID 60%  
COVERAGE

**INSULATION MATERIAL AND DIAMETER**

GAS INJECTED FOAM POLYETHYLENE Ø.180"  
NOMINAL

**JACKET MATERIAL AND DIAMETER**

BLACK PVC; Ø.270 NOMINAL

**OPERATING TEMPERATURE:**

-10°C - +70°C MIN

**NOTE:**

SEE ASSEMBLY INSTRUCTIONS ASI-0026.DOC