

**Bulk Cable Specification**

MODEL	PRIMARY PACKAGING	SECONDARY PACKAGING	LENGTH
CS15-100	COIL	BOX	100 FT.
CS15-500	SPOOL	STRETCH WRAP	500 FT.
CS15-1K	SPOOL	STRETCH WRAP	1,000 FT.

Specification			UL2464	Construction DWG.
Construction Item			Component A	
Conductor	Construction AWG	AWG	24	
	Material	-	TINNED COPPER	
Drain Wire	Construction AWG	AWG	24	
	Material	-	STRANDED TINNED COPPER	<b>Color Code</b> 1. BLACK 2. WHITE 3. RED 4. GREEN 5. ORANGE 6. BLUE 7. WHITE/BLACK 8. RED/BLACK 9. GREEN/BLACK 10. ORANGE/BLACK 11. BLUE/BLACK 12. BLACK/WHITE 13. RED/WHITE 14. GREEN/WHITE 15. BLUE/WHITE
Outside Tape	Material	-	ALUMINUM/MYLAR FOIL	
Jacket	Material	-	PVC	
	Diameter	mm	Ø.275" [7]	
	Color	-	CHROME GRAY	
<b>Electrical Characteristics</b>			<b>Physical Characteristics of Jacket</b>	<b>Cable Marking</b>
RATINGS: 300V, 80°C			N/A	N/A
			<b>Regulatory Compliance:</b> [CE2011/65/EU(RoHS DIRECTIVE, etc.)]	

(Information subject to change without notice)