


THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT WRITTEN PERMISSION OF L-COM, INC IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
E	ECN 4397: CHANGE SUPPLIER UL MARKING ON JACKET	11/20/09	DLF

Cross-sectional View



Color Code

- P1. White – White/Black
- P2. Red – Red/Black
- P3. Yellow – Yellow/Black
- P4. Green – Green/Black
- P5. Blue – Blue/White

ITEM	DESCRIPTION
Conductor	No. of Conductors: 5 Pairs
	Material: Tinned Copper Wire Stranded
	Construction: 26 AWG; 7 strands, .006"
Insulation	Material: SR-PVC
	Nominal Thickness: .010"
	Nominal Diameter: .039"
Shielding	Material: Aluminized Mylar (spirally wrapped)
	Coverage: 100% coverage with 25% overlap
Drain Wire	Material: Tinned Copper Wire Stranded
	Construction: 26 AWG; 7 strands, .006"
Braiding	Material: Tinned Copper Wire
	Coverage: 85% overlapping
Jacket	Material: 80°C PVC
	Nominal Thickness: .039"
	Nominal Diameter: .276"
	Color: Light Gray

Marking:

<SUPPLIER UL FILE NUMBER>  AWM STYLE 2464 80°C 300V VW-1

ELECTRICAL PROPERTIES

Conductor Resistance	Max 148 ohms/km at 20°C
Insulation Resistance	Min 100 Megohms-km at 20°C
Dielectric test	1500VAC /1min. No Breakdown



45 BEECHWOOD DRIVE
NORTH ANDOVER, MA 01845

	APPROVALS	DATE		
DRAWN BY	D. PARHAM	4/23/2002	CABLE SPECIFICATION	DOCUMENT NUMBER CSTP5
CHECKED BY	T. CLARK	4/23/2002		
APPROVED BY	C. McCORMICK	4/23/2002		
				REV E