PROPRIETARY NOTICE

This document discloses confidential subject matter in which MilesTek Corporation and its subsidiaries have proprietary rights. Neither receipt nor possession thereof confers or transfers any right to reproduce or disclose the document, any part thereof, any information contained therein, or any physical article or device, or to practice any method or process, except by written permission from, or written agreement with MilesTek Corporation and its subsidiaries.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	REV A DRAWING RELEASED	05/15/2019	DFRISIELLO



Note:

Electrical:
Impedance: 75 ohm
Frequency Range: 0~12 GHz.
Voltage Rating: 500 V rms.
Insulator Resistance: ≥5 GΩ
Dielectric Withstanding Voltage: 1000 V rms.
Contact Resistance: Center Contact ≤3 mΩ.
Outer Contact ≤2.5 mΩ.

Environmental:
Temperature Range: -65ɑ to 165ɑ
Corrosion(Salt Spray): MIL-STD-202, Method 101, Cond. B
Thermal Shock: MIL-STD-202, Method 107, Cond. B
Mechanical: MIL-STD-202, Method 213, Cond. I
Vibration: MIL-STD-202, Method 204, Cond. D

PACKAGING:
CONNECTOR SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH SPECIFICATION PS-0054.

REGULATORY COMPLIANCE:
EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION)



Recommended Cable Stripping Dimensions



Recommended Crimping Dimensions for Ferrule

ITEM	Description	Material	Finish
6	Round Nut	Brass	NICKEL PLATE
5	O-Ring	NBR	Black
4	Ferrule	Brass	NICKEL PALTE
3	Inner Contact	BeCu	NICKEL/GOLD PLATE
2	Insulator	PTFE	None
1	Body	Brass	NICKEL PLATE

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES

OVERALL CABLE LENGTH TOLERANCE:
≤12 [305] = +1 [25] / -0
>12 [305] ≤60 [1524] = +2 [51] / -0
>60 [1524] ≤120 [3048] = +4 [102] / -0
>120 [3048] ≤300 [7620] = +6 [152] / -0
>300 [7620] = +5% / -0%

ALL OTHER DIMENSIONAL TOLERANCES:
.X = ± .2 [5.08]
.XX = ± .02 [.51]
.XXX = ±.005 [.13]

CUSTOMER REFERENCE DOCUMENT:

SIGNATURE	DATE
DRAWN BY: GHUAN	05/13/2019
CHECKED BY: DFRISIELLO	05/14/2019
APPROVED BY: DFRISIELLO	05/14/2019

CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY

CAGE CODE: 4Z977

MilesTek
Military | Aerospace | Communications | Industrial

MILESTEK CORPORATION
301 LEORA LANE, SUITE 100
LEWISVILLE, TX 75056
PHONE: (940) 484-9400
FAX: (940) 566-1047

TITLE
Ultra Tiny BNC Crimp Jack for Belden 1855A

SIZE	DRAWING NUMBER:	REV.
A	MAVB00006	A

SCALE: NTS | SHEET 1 OF 1