

8

7

6

5

4

3

2

1

PROPRIETARY NOTICE

This document discloses confidential subject matter in which MilesTek Corporation and its subsidiaries have proprietary rights. Neither receipt nor possession thereof confers or transfers any right to reproduce or disclose the document, any part thereof, any information contained therein, or any physical article or device, or to practice any method or process, except by written permission from, or written agreement with MilesTek Corporation and its subsidiaries.

MDA00041

A

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	06/12/17	J.YOU

2X 4-40 UNC-2A  
METAL THUMBSCREW

LENGTH

MOLDED HOOD,  
LSZH, BLACK

MOLDED HOOD,  
LSZH, BLACK

"P1"

PIN 1






2X 4-40 UNC-2A  
THUMBSCREW

2X MALE DVI-D  
SINGLE LINK  
CONNECTOR

PIN 1

"P2"

U.L. STYLE 21100,  
(4) 30AWG INDIVIDUALLY SHIELDED TWISTED PAIRS,  
(5) 28AWG CONDUCTORS, OVERALL ALUMINIZED  
POLYESTER FILM SHIELD PLUS TINNED COPPER BRAID SHIELD,  
JACKET: LOW SMOKE ZERO HALOGEN, BLACK



SHELL SHELL (SHIELD DRAIN WIRE)

PIN 8 NO CONNECTION

**NOTES:**

1. CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
2. CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH SPECIFICATION PS-0054.
3. DUST COVERS INSTALLED FOR SHIPPING (NOT SHOWN).

**REGULATORY COMPLIANCE:**

CE2011/65/EU(RoHS DIRECTIVE)

MODEL NUMBER	LENGTH	
	FEET	METERS
MDA00041-1F	1.0	.31
MDA00041-3F	3.0	.91
MDA00041-5F	5.0	1.52
MDA00041-10F	10.0	3.05
MDA00041-15F	15.0	4.57

**NON CONTROLLED DRAWING IF PRINTED**

AS9100C CERTIFIED			CAD SYSTEM DRAWING - DO NOT REVISE MANUALLY			
DASH	NEXT ASSY	USED ON	UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES	SIGNATURE	DATE	 MILESTEK CORPORATION 1506 INTERSTATE 35 WEST DENTON, TX 76207 PHONE: 866.524.1553 FAX: 940.591.7086
			OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0%  ALL OTHER DIMENSIONAL TOLERANCES: .X = ±.2 [5.08] .XX = ±.02 [51] .XXX = ±.005 [13]	DRAWN BY: J.YOU 06/12/17  CHECKED BY: B.GATES 06/12/17  APPROVED ENGINEERING: S.PAN 06/12/17  APPROVED MANUFACTURING:   CUSTOMER APPROVAL	TITLE CA-DVI SL M/M RA LFT EXIT LSZH	
APPLICATION			CUSTOMER REFERENCE DOCUMENT:	CAGE CODE: 42977	SCALE: NTS	DRAWING NUMBER: MDA00041 SHEET 1 OF 1

8

7

6

5

4

3

2

1