

Assemblies Using TWC-124-2 Large Diameter (0.25 inch) 124 Ohm Twinaxial Cable

NEW

TRB 3-Slot Plug to TRB 3-Slot Plug		
xxx = length in inches		
10-06030-210	Part Number: MP-2205-xxx	10-06030-210
TRB 3-Slot Plug to Blunt		
xxx = length in inches		
10-06030-210	Part Number: MP-2302-xxx	Blunt
TRB 3-Slot Plug w/ Bend Relief to TRB 3-Slot Plug w/ Bend Relief		
xxx = length in inches		
10-06033-210	Part Number: MP-2152-xxx	10-06033-210
TRB 3-Slot Plug to TRB 3-Lug Jack		
xxx = length in inches		
10-06030-210	Part Number: MP-2600-xxx	10-06575-210
TRB 3-Lug Jack to TRB 3-Lug Jack		
xxx = length in inches		
10-06575-210	Part Number: MP-2601-xxx	10-06575-210

Tech Note: See cable specifications on page 116**TWC-124-2 Connectors****A****B****C**

KEY	PART NUMBER	DESCRIPTION
A	10-06030-210	3-Slot TRB Male Solder Clamp Plug
B	10-06033-210	3-Slot TRB Male Solder Clamp Plug With Bend Relief
C	10-06575-210	3-Lug TRB Female Solder Clamp Jack

Assemblies Using TWC-124-1A Small Diameter (0.155 inch) 124 Ohm Twinaxial Cable

TRB 3-Slot Plug to TRB 3-Slot Plug		
xxx = length in inches		
10-06030-231	Part Number: MP-2292-xxx	10-06030-231
TRB 3-Slot Plug to Blunt		
xxx = length in inches		
10-06030-231	Part Number: MP-2602-xxx	Blunt
TRB 3-Slot Plug w/ Bend Relief to TRB 3-Slot Plug w/ Bend Relief		
xxx = length in inches		
10-06033-231	Part Number: MP-2487-xxx	10-06033-231
TRS 3-Slot Plug to TRS 3-Slot Plug		
xxx = length in inches		
10-10030-231	Part Number: MP-2603-xxx	10-10030-231
TRS 3-Slot Plug to TRB 3-Slot Plug		
xxx = length in inches		
10-10030-231	Part Number: MP-2344-xxx	10-06030-231

Tech Note: See cable specifications on page 116**TWC-124-1A Connectors****D****E****F****G**

KEY	PART NUMBER	DESCRIPTION
D	10-06030-231	3-Slot TRB Male Solder Clamp Plug
E	10-06033-231	3-Slot TRB Male Solder Clamp Plug With Bend Relief
F	10-06575-231	3-Lug TRB Female Solder Clamp Jack
G	10-10030-231	3-Slot TRS Subminiature Male Solder Clamp Plug