



PROPRIETARY NOTICE
This document discloses confidential subject matter in which MilesTek Corporation and its subsidiaries have proprietary rights. Neither receipt nor possession thereof confers or transfers any right to reproduce or disclose the document, any part thereof, any information contained therein, or any physical article or device, or to practice any method or process, except by written permission from, or written agreement with MilesTek Corporation and its subsidiaries.

LEAD FREE SOLDER

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	01/28/2019	DFRISIELLO



MODEL NUMBER	LENGTH METERS [FEET]
MSA00459-03M	0.3 [1.0]
MSA00459-05M	0.5 [1.64]
MSA00459-075M	0.75 [2.46]
MSA00459-1M	1.0 [3.28]
MSA00459-2M	2.0 [6.56]
MSA00459-3M	3.0 [9.84]
MSA00459-4M	4.0 [13.12]
MSA00459-6M	6.0 [19.69]

NOTES:

- *XXX = LENGTH IN INCHES
*XXXM = LENGTH IN METERS
- CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
- ALL MATERIALS USED ARE CERTIFIED RoHS COMPLIANT.

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES	SIGNATURE		DATE	<div>MilesTek</div> <div>Military Aerospace Communications Industrial</div>	MILESTEK CORPORATION 301 LEORA LANE, SUITE 100 LEWISVILLE, TX 75056 PHONE: (940) 484-9400 FAX: (940) 566-1047	
OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤40 [1024] = +2 [51] / -0 >40 [1024] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0%	DRAWN BY: DFRISIELLO	01/28/2019				
	CHECKED BY: MHEARN	01/28/2019				
	APPROVED BY: MHEARN	01/28/2019				
ALL OTHER DIMENSIONAL TOLERANCES: X = ±.2 [5.08] XX = ±.02 [1.27] XXX = ±.005 [1.27]	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY			TITLE LEAD FREE HT TWNX SUBM P-SUBM THRD P		
	CUSTOMER REFERENCE DOCUMENT:			SIZE <div>A</div>	DRAWING NUMBER: <div>MSA00459</div>	REV. <div>A</div>
CAGE CODE: 4Z977			SCALE: NTS SHEET 1 OF 1			