



SMB Plug to SMB Jack Bulkhead Mount Using Flexible RG316-DS Coax Cable

RF Cable Assemblies Technical Data Sheet

MTCA00101

Configuration

- Connector 1: SMB Plug
- Connector 2: SMB Jack Bulkhead
- Cable Type: RG316-DS

Features

- Max Frequency 3 GHz
- 70% Phase Velocity
- Double Shielded
- FEP Jacket

Applications

- General Purpose
- Laboratory Use

Description

MilesTek's MTCA00101 coaxial cable assembly is a SMB plug to SMB jack bulkhead mount using flexible RG316-DS coax cable. MilesTek cables are built using high quality materials and are tested to insure these assemblies meet all performance specifications. Coaxial cable assemblies are stocked in standard lengths and will ship same day. Custom lengths of this cable assembly are also available upon request. These assemblies are part of MilesTek's extensive portfolio of products that are in stock and ship same day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		3	GHz
VSWR			1.4:1	
Velocity of Propagation		70		%
Capacitance		29.4 [96.46]		pF/ft [pF/m]
Operating Voltage (AC)			335	Vrms

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	0.1	0.4	1	3		GHz
Insertion Loss (Typ.)	0.115	0.172	0.3	0.545		dB/ft dB/m
	0.38	0.56	0.98	1.79		

Electrical Specification Notes:

Insertion Loss does not include the loss of the connectors. Insertion Loss is estimated as 0.1 dB per connector.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMB Plug to SMB Jack Bulkhead Mount Using Flexible RG316-DS Coax Cable MTCA00101](#)



SMB Plug to SMB Jack Bulkhead Mount Using Flexible RG316-DS Coax Cable

RF Cable Assemblies Technical Data Sheet

MTCA00101

Mechanical Specifications

Cable Assembly

Diameter	0.256 in [6.5 mm]
Weight	0.027 lbs [12.25 g]

Cable

Cable Type	RG316-DS
Impedance	50 Ohms
Inner Conductor Type	Stranded
Inner Conductor Material and Plating	Copper Clad Steel, Silver
Dielectric Type	PTFE
Number of Shields	2
Shield Layer 1	Silver Plated Copper Braid
Shield Layer 2	Silver Plated Copper Braid
Jacket Material	FEP, Tan
Jacket Diameter	0.114 in [2.9 mm]
One Time Minimum Bend Radius	0.59 in [14.99 mm]

Connectors

Description	Connector 1	Connector 2
Type	SMB Plug	SMB Jack Bulkhead
Specification	MIL-STD-348A	MIL-STD-348A
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Beryllium Copper, Gold	Brass, Gold
Contact Plating Specification	30μ in. minimum	30μ in. minimum
Dielectric Type	Teflon	Teflon
Body Material and Plating	Brass, Nickel	Brass, Nickel
Body Plating Specification	100μ in. minimum	100μ in. minimum

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

- Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMB Plug to SMB Jack Bulkhead Mount Using Flexible RG316-DS Coax Cable MTCA00101](#)



SMB Plug to SMB Jack Bulkhead Mount Using Flexible RG316-DS Coax Cable

RF Cable Assemblies Technical Data Sheet

MTCA00101

How to Order

Part Number Configuration:

MTCA00101

- **xx**

uu

Unit of Measure:

cm = Centimeters

<blank> = Inches

Length

Base Number

Example: MTCA00101-12 = 12 inches long cable
MTCA00101-100cm = 100 cm long cable

Our offering, used primarily in military, R&D and production applications, consists of a comprehensive line of MIL-STD-1553B data bus couplers, harnesses and cable assemblies, connectors and connector termination systems. MilesTek also offers expertise in manufacturing custom cable assemblies and harnesses.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMB Plug to SMB Jack Bulkhead Mount Using Flexible RG316-DS Coax Cable MTCA00101](https://www.milestek.com/SMB-Plug-SMB-Jack-MTRG316DS--MTCA00101-p.aspx)

URL: <https://www.milestek.com/SMB-Plug-SMB-Jack-MTRG316DS--MTCA00101-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. MilesTek reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. MilesTek does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and MilesTek does not assume any liability arising out of the use of any part or documentation.

MTCA00101 CAD Drawing

SMB Plug to SMB Jack Bulkhead Mount Using Flexible RG316-DS Coax Cable

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	09/25/2019	SELLIS

LENGTH
(CONTACT TO FLANGE)

2X SHRINK TUBE,
BLACK

MTRG316DS/U

SMB JACK
BULKHEAD

SMB PLUG

RECOMMENDED
PANEL CUTOUT

UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE INCHES
DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:
X = ±2 [5.08] FRACTIONS ± 1/32
XX = ±.02 [.51]
XXX = ±.005 [.13] ANGLES ± 1°

OVERALL CABLE LENGTH (L) TOLERANCES:
L ≤ 12 [305] = +1 [25] / -0
12 [305] < L ≤ 60 [1524] = +2 [51] / -0
60 [1524] < L ≤ 120 [3048] = +4 [102] / -0
120 [3048] < L ≤ 300 [7620] = +6 [152] / -0
300 [7620] < L = +5% / -0

ALL DIMENSIONS SHOWN
ARE FOR REFERENCE ONLY.

THIRD-ANGLE PROJECTION

THE INFORMATION AND
DESIGN IN THIS DOCUMENT IS
THE PROPERTY OF
MILESTEK CORPORATION.
ALL RIGHTS RESERVED.

SHEET 1 OF 1
SCALE N/A
REV A

MILESTEK
an INFINITE brand
301 Leora Ln., Suite 100, Lewisville, TX 75056
Phone: 1.940.484.9400 | 1.866.524.1553
Fax: 1.972.394.7913
www.milestek.com | e-mail: Customerfirst@milestek.com

CAGE CODE DRAWN BY PART NUMBER
A 4Z977 DFRISIELLO MTC00101

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

T-Rev C