



SMB Jack to SMB Jack Using Flexible RG316-DS Coax Cable

RF Cable Assemblies Technical Data Sheet

MTCA00103

Configuration

- Connector 1: SMB Jack
- Connector 2: SMB Jack
- Cable Type: RG316-DS

Features

- 70% Phase Velocity
- Double Shielded
- FEP Jacket

Applications

- General Purpose
- Laboratory Use

Description

MilesTek's MTCA00103 coaxial cable assembly is a SMB jack to SMB jack using flexible RG316-DS coax cable. MilesTek cables are built using high quality materials and are tested to insure these assemblies meet all performance specifications. Coaxial cable assemblies are stocked in standard lengths and will ship same day. Custom lengths of this cable assembly are also available upon request. These assemblies are part of MilesTek's extensive portfolio of products that are in stock and ship same day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
VSWR			1.4:1	
Velocity of Propagation		70		%
Capacitance		29.4 [96.46]		pF/ft [pF/m]
Operating Voltage (AC)			335	Vrms

dB/m

Electrical Specification Notes:

Insertion Loss does not include the loss of the connectors. Insertion Loss is estimated as 0.1 dB per connector.

Mechanical Specifications

Cable Assembly

Diameter 0.25 in [6.35 mm]

Weight 0.028 lbs [12.7 g]

Cable

Cable Type RG316-DS

Impedance 50 Ohms

Inner Conductor Type Stranded

Inner Conductor Material and Plating Copper Clad Steel, Silver

Dielectric Type PTFE

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMB Jack to SMB Jack Using Flexible RG316-DS Coax Cable MTCA00103](#)



SMB Jack to SMB Jack Using Flexible RG316-DS Coax Cable

RF Cable Assemblies Technical Data Sheet

MTCA00103

Number of Shields	2
Shield Layer 1	Silver Plated Copper Braid
Shield Layer 2	Silver Plated Copper Braid
Jacket Material	FEP, Tan
Jacket Diameter	0.114 in [2.9 mm]
One Time Minimum Bend Radius	0.59 in [14.99 mm]

Connectors

Description	Connector 1	Connector 2
Type	SMB Jack	SMB Jack
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Brass, Gold	Brass, Gold
Contact Plating Specification	30 μ in. Minimum	30 μ in. Minimum
Dielectric Type	PTFE	PTFE
Body Material and Plating	Brass, Nickel	Brass, Nickel
Body Plating Specification	100 μ in. Minimum	100 μ in. Minimum

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

- Values at 25°C, sea level.

How to Order

Part Number Configuration:

MTCA00103

- **xx** **uu**

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: MTCA00103-12 = 12 inches long cable
MTCA00103-100cm = 100 cm long cable

Our offering, used primarily in military, R&D and production applications, consists of a comprehensive line of MIL-STD-1553B data bus couplers, harnesses and cable assemblies, connectors and connector termination systems. MilesTek also offers expertise in manufacturing custom cable assemblies and harnesses.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMB Jack to SMB Jack Using Flexible RG316-DS Coax Cable MTCA00103](#)

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMB Jack to SMB Jack Using Flexible RG316-DS Coax Cable MTCA00103](#)



SMB Jack to SMB Jack Using Flexible RG316-DS Coax Cable

RF Cable Assemblies Technical Data Sheet

MTCA00103

URL: <https://www.milestek.com/SMB-Jack-SMB-Jack-MTRG316DS-MTCA00103-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. MilesTek reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. MilesTek does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and MilesTek does not assume any liability arising out of the use of any part or documentation.

MilesTek
an INFINITE[®] brand

MTCA00103 CAD Drawing

SMB Jack to SMB Jack Using Flexible RG316-DS Coax Cable

