



SMB Plug 50 Ohm Coax Connector Crimp Attachment for RG174, RG316, RG188, LMR-100

RF Connectors Technical Data Sheet

MTCN0035

Configuration

- SMB Plug Connector
- MIL-STD-348A
- 50 Ohms
- Straight Body Geometry
- RG174, RG316, RG188, LMR-100 Interface Type
- Crimp/Solder Attachment

Applications

- General Purpose Test
- Custom Cable Assemblies

Description

MilesTek RF SMB connector will ship the same day as purchased from our broad selection of military, aerospace and industrial radio frequency components. Our SMB connector terminates to a coax interface which includes RG174, RG316, RG188 and LMR-100. This SMB connector for coax has a 50 Ohm impedance and is just one part of our large, in-stock inventory.

Part number MTCN0035 SMB connector from MilesTek is a plug gender (also known as male). This RF connector from MilesTek has a 3 GHz maximum frequency. Our 3 GHz SMB connector maximum frequency applies to RG174, RG316, RG188 and LMR-100 interfaces but may vary between them. Our radio frequency SMB plug (male) crimp/solder connector is in-stock and does ship same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		3	GHz
VSWR			1.37:1	
Operating Voltage (AC)			335	Vrms

Mechanical Specifications

Size	
Length	0.85 in [21.59 mm]
Width/Dia.	0.256 in [6.50 mm]
Weight	0.012 lbs [5.44 g]

Material Specifications

Description	Material	Plating
Contact	Beryllium Copper	Gold 30 µin minimum
Insulation	PTFE	
Body	Brass	Nickel 100 µin minimum
Coupling Nut	Brass	Nickel 100 µin minimum

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMB Plug 50 Ohm Coax Connector Crimp Attachment for RG174, RG316, RG188, LMR-100 MTCN0035](#)



SMB Plug 50 Ohm Coax Connector Crimp Attachment for RG174, RG316, RG188, LMR-100

RF Connectors Technical Data Sheet

MTCN0035

Crimp Sleeve	Brass	Nickel
[Redacted]		

Environmental Specifications

Temperature

Operating Range

-65 to 165 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Our offering, used primarily in military, R&D and production applications, consists of a comprehensive line of MIL-STD-1553B data bus couplers, harnesses and cable assemblies, connectors and connector termination systems. MilesTek also offers expertise in manufacturing custom cable assemblies and harnesses.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMB Plug 50 Ohm Coax Connector Crimp Attachment for RG174, RG316, RG188, LMR-100 MTCN0035](#)

URL:

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. MilesTek reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. MilesTek does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and MilesTek does not assume any liability arising out of the use of any part or documentation.

MTCN0035 CAD Drawing

SMB Plug 50 Ohm Coax Connector Crimp Attachment for RG174, RG316, RG188, LMR-100



MilestTek
an INFINITE brand

301 Leora Ln., Suite 100, Lewisville, TX 75066
Phone: 1.940.484.9400 | 1.866.524.1553
www.milesttek.com | e-mail: Customerfms@milesttek.com

SHEET 1 OF 1
SCALE N/A

DRAWN BY: KDANG
PART NUMBER: MTCN0035
REV: A

UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE IN INCHES
DIMENSIONS IN [] ARE IN MILLIMETERS

TOLERANCES:
.X±.2 [5.08] FRACTIONS ± 1/32
.XX±.01 [.25] ANGLES ± 1°
XXX±.005 [.13] ARE FOR REFERENCE ONLY.

THRU-ANGLE PROJECTION

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.