



SMB Jack Bulkhead Mount 50 Ohm Coax Connector Crimp Attachment for RG188-DS, RG316-DS

RF Connectors Technical Data Sheet

MTCN0047

Configuration

- SMB Jack Connector
- MIL-STD-348A
- 50 Ohms
- Straight Body Geometry

- RG188-DS, RG316-DS Interface Type
- Crimp/Solder Attachment
- Bulkhead

Applications

General Purpose Test

Rack and Panel Mount Applications

Custom Cable Assemblies

Description

MilesTek RF SMB bulkhead connector will ship the same day as purchased from our broad selection of military, aerospace and industrial radio frequency components. Our bulkhead SMB connector terminates to a coax interface which includes RG188-DS and RG316-DS. This bulkhead SMB connector for coax has a 50 Ohm impedance and is just one part of our large, in-stock inventory.

Part number MTCN0047 SMB connector from MilesTek is a jack gender (also known as female). This RF connector from MilesTek has a 4 GHz maximum frequency. Our 4 GHz SMB connector maximum frequency applies to RG188-DS and RG316-DS interfaces but may vary between them. Our radio frequency SMB jack (female) crimp/solder connector is in-stock and does ship same-day.

Electrical Specifications

| Description | Minimum | Typical | Maximum | Units |
|--------------------------------------|---------|---------|---------|-------|
| Frequency Range | DC | 20 | 4 | GHz |
| Operating Voltage (AC) | | 10 | 335 | Vrms |
| Dielectric Withstanding Voltage (AC) | | | 1,000 | Vrms |
| | | | | |

Mechanical Specifications

Size

 Length
 1 in [25.4 mm]

 Width/Dia.
 0.25 in [6.35 mm]

 Weight
 0.005 lbs [2.27 g]

Material Specifications

| Description | Material | Plating | |
|-------------|----------|----------------------------|--|
| Contact | Brass | Gold 30µ in. minimum | |
| Insulation | Teflon | | |
| Body | Brass | Nickel 100u in. minimum | |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMB Jack Bulkhead Mount 50 Ohm Coax Connector Crimp Attachment for RG188-DS, RG316-DS MTCN0047





SMB Jack Bulkhead Mount 50 Ohm Coax Connector Crimp Attachment for RG188-DS, RG316-DS

RF Connectors Technical Data Sheet

MTCN0047

Environmental Specifications Temperature

Operating Range

-65 to 165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Our offering, used primarily in military, R&D and production applications, consists of a comprehensive line of MIL-STD-1553B data bus couplers, harnesses and cable assemblies, connectors and connector termination systems. MilesTek also offers expertise in manufacturing custom cable assemblies and harnesses.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMB Jack Bulkhead Mount 50 Ohm Coax Connector Crimp Attachment for RG188-DS, RG316-DS MTCN0047

URL:

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. MilesTek reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. MilesTek does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and MilesTek does not assume any liability arising out of the use of any part or documentation.

MTCN0047 CAD Drawing

SMB Jack Bulkhead Mount 50 Ohm Coax Connector Crimp Attachment for RG188-DS, RG316-DS

