



## SMB Jack Bulkhead Mount 50 Ohm Coax Connector Crimp Attachment for RG174, RG316, RG188, LMR-100

### RF Connectors Technical Data Sheet

MTCN0049

#### Configuration

- SMB Jack Connector
- MIL-STD-348A
- 50 Ohms
- Straight Body Geometry
- RG174, RG316, RG188, LMR-100 Interface Type
- Crimp/Solder Attachment
- Bulkhead

#### Applications

- General Purpose Test
- Rack and Panel Mount Applications
- Custom Cable Assemblies

#### Description

MilesTek RF SMB bulkhead connector will ship the same day as purchased from our broad selection of military, aerospace and industrial radio frequency components. Our bulkhead SMB connector terminates to a coax interface which includes RG174, RG316, RG188 and LMR-100. This bulkhead SMB connector for coax has a 50 Ohm impedance and is just one part of our large, in-stock inventory.

Part number MTCN0049 SMB connector from MilesTek is a jack gender (also known as female). This RF connector from MilesTek has a 4 GHz maximum frequency. Our 4 GHz SMB connector maximum frequency applies to RG174, RG316, RG188 and LMR-100 interfaces but may vary between them. Our radio frequency SMB jack (female) crimp/solder connector is in-stock and does ship same-day.

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		4	GHz
VSWR			1.3:1	
Operating Voltage (AC)			335	Vrms

#### Mechanical Specifications

<b>Size</b>	
Length	0.867 in [22.02 mm]
Width/Dia.	0.25 in [6.35 mm]
Weight	0.005 lbs [2.27 g]

#### Material Specifications

Description	Material	Plating
Contact	Brass	Gold 30 µin minimum
Insulation	PTFE	
Body	Brass	Nickel 100 µin minimum

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMB Jack Bulkhead Mount 50 Ohm Coax Connector Crimp Attachment for RG174, RG316, RG188, LMR-100 MTCN0049](#)



## SMB Jack Bulkhead Mount 50 Ohm Coax Connector Crimp Attachment for RG174, RG316, RG188, LMR-100

### RF Connectors Technical Data Sheet

MTCN0049

#### Environmental Specifications

##### Temperature

Operating Range

-65 to 165 deg C

**Compliance Certifications** (see [product page](#) for current document)

#### Plotted and Other Data

Notes:

Our offering, used primarily in military, R&D and production applications, consists of a comprehensive line of MIL-STD-1553B data bus couplers, harnesses and cable assemblies, connectors and connector termination systems. MilesTek also offers expertise in manufacturing custom cable assemblies and harnesses.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMB Jack Bulkhead Mount 50 Ohm Coax Connector Crimp Attachment for RG174, RG316, RG188, LMR-100 MTCN0049](#)

URL:

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. MilesTek reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. MilesTek does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and MilesTek does not assume any liability arising out of the use of any part or documentation.

# MTCN0049 CAD Drawing

## SMB Jack Bulkhead Mount 50 Ohm Coax Connector Crimp Attachment for RG174, RG316, RG188, LMR-100

